



SHAKE WELL BEFORE USING FEATURES

ICE BREAKER is new technology that immediately freezes and shrinks seized and corroded nuts, bolts, pins, hinges, and studs allowing the lubricant to penetrate and loosen the toughest applications. Spraying a liberal amount on the area will allow **ICE BREAKER** to reach deeper in the toughest of applications, work more successfully than other penetrants, and will also shield against renewed corrosion. Use in oil rigs, factories, automotive repair centers, manufacturing plants, machine shops, and anywhere corrosion is a big problem.

DIRECTIONS FOR USE

1. Shake well before using.
2. Spray liberal amount on area to be treated. Part should be ready to loosen after 30 seconds.
3. Reapply as needed.

Sudden drop in temperature after spraying may result in cracking of some paint and plastic. Test in an inconspicuous area before applying.

COMPOSITIONAL INFORMATION

Contains Difluoroethane (CAS# 75-37-6), Polydimethylsiloxane (CAS# 63148-62-9), Methyl Isobutyl Ketone (CAS#108-10-1)

DANGER: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Harmful if inhaled. Causes serious eye irritation. May cause drowsiness or dizziness.



PRECAUTIONARY STATEMENT

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Avoid breathing vapors or spray. Use only outdoors or in a well-ventilated area. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves and eye protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Read Safety Data Sheet before using.
KEEP OUT OF REACH OF CHILDREN.**

Made in U.S.A. with globally sourced materials.
VOC Content 4.0%

⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Alan Environmental Products, Inc.

509 S 1st St. · Monmouth, IL 61462-2230
800-991-3765

www.alanenvironmental.com



ICE BREAKER

FREEZING PENETRATING LUBRICANT

Part# AE 141

**FREEZING ACTION UNLOCKS RUSTED PARTS
NON-CONDUCTIVE • NON-CHLORINATED
LOW VOC CONTENT**



DANGER:

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. HARMFUL IF INHALED. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. Read additional precautions on rear panel.

NET WT. 9 OZ. (255 grams)