Safety Data Sheet

SECTION 1: Product and company identification

Product name : Bio Coil Cleaner

Use of the substance/mixture : Aerosol Cleaner
Product code : AE 100

Company : Alan Environmental Products Inc.

PO Box 934

Monmouth, IL 61462 - USA

T (800) 991-3765

Emergency number : INFOTRAC 24 HR. CHEMICAL EMERGENCY NO.: (800) 535-5053

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Eye Irrit. 2A H319 Skin Sens. 1 H317

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





602 GHS

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol May cause an allergic skin reaction

May cause an allergic skin rea Causes serious eye irritation

Precautionary statements (GHS-US) : Keep away from heat, hot surfaces, Do not smoke, open flames, sparks. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Avoid breathing dust, fume, gas, mist, spray, vapors

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace Wear protective gloves, protective clothing, eye protection, face protection

If on skin: Wash with plenty of water

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Specific treatment (see First aid measures on this label)
If skin irritation or rash occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash it before reuse

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

 Date of issue: 12/4/2015
 Revision date: 03/24/2015
 Version: 1.0
 P GHS SDS
 Page 1 of 8

Safety Data Sheet

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
Glycol Ether EB	(CAS No) 111-76-2	1 - 2.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
propane	(CAS No) 74-98-6	1 - 2.5	Flam. Gas 1, H220 Compressed gas, H280
Diethylene Glycol Monoethyl Ether	(CAS No) 111-90-0	1 - 2.5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
tetrasodium ethylenediaminetetracetate	(CAS No) 64-02-8	1 - 2.5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
(+)-limonene	(CAS No) 5989-27-5	0.1 - 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

For minor skin contact, avoid spreading material on unaffected skin.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes serious eye irritation. May cause an allergic skin reaction. Extremely flammable.

Symptoms/injuries after inhalation : Irritation of the nasal mucous membranes. Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Under fire conditions closed containers may rupture or explode.

Explosion hazard : Contents under pressure. Pressurized container: may burst if heated.

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Move containers away from the fire area if this can

be done without risk. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire

burn out.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stay upwind/keep distance from source. Evacuate unnecessary personnel. Vapors may travel long

distances along ground before igniting/flashing back to vapor source.

 Date of issue: 12/4/2015
 Revision date: 03/24/2015
 Version: 1.0
 P GHS SDS
 Page 2 of 8

Safety Data Sheet

6.1.1. For non-emergency personnel

: Do not enter without an appropriate protective equipment. Advice local authorities if considered Protective equipment

necessary. DO NOT touch spilled material. Ventilate the area thoroughly, especially low lying areas

(basements, work pits etc.).

Do not breathe gas. Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area. **Emergency procedures**

6.1.2. For emergency responders

Protective equipment Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

Environmental precautions

Avoid release to the environment. Advice local authorities if considered necessary. Stop leak if safe to do so. Do not contaminate water with the product or its container. Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

Methods and material for containment and cleaning up

For containment Eliminate every possible source of ignition. Prevent the product from entering drains or confined

areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Form with air vapors (heavier than air) who stay on the floor. Stop leak if safe to do so. Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid. Isolate area until gas has dispersed. Collect

spillage.

Methods for cleaning up Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Dispose as

hazardous waste.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed Do not use if spray button is missing or defective. Pressurized container: Do not pierce or burn, even

after use. Keep away from heat, sparks and flame.

Avoid prolonged and repeated contact with skin. Intentional misuse by deliberately concentrating and Precautions for safe handling

inhaling may be harmful or fatal. Do not breathe gas/vapor/aerosol. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Ground/bond container and receiving equipment. Do not re-use empty containers. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Observe normal hygiene standards. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when

leaving work. Do not discharge the waste into the drain.

Hygiene measures : Wash thoroughly after handling

Conditions for safe storage, including any incompatibilities

Pressurized container. Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, Technical measures

sparks, open flames and other ignition sources. No smoking

Storage conditions Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep cool. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures

exceeding 50 °C/ 122 °F. Refrigerate.

Storage temperature < 49 °C Storage area Aerosol 1.

SECTION 8: Exposure controls/personal protection

Control parameters

Glycol Ether EB (111-76-2)			
ACGIH	ACGIH TWA (ppm)	20 ppm	
ACGIH	Remark (ACGIH)	Eye & URT irr	
propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
butane (106-97-8)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
ACGIH	ACGIH STEL (ppm)	1000 ppm	

Date of issue: 12/4/2015 Revision date: 03/24/2015 Version: 1.0 P GHS SDS Page 3 of 8

Safety Data Sheet

8.2. Exposure controls

Appropriate engineering controls

Personal protective equipment

- Ensure good ventilation of the work station.
- Gloves. Protective goggles. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Aerosol. Clear, colorless liquid.

Odor : characteristic
Odor threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : 212 °F Estimated

Flash point : -156 °F Propellant estimated

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available Explosive properties No data available : No data available Oxidizing properties Vapor pressure : No data available Relative density No data available : No data available Relative vapor density at 20 °C Specific gravity / density : 0.969 g/ml : No data available Solubility Log Pow : No data available No data available Log Kow Auto-ignition temperature No data available Decomposition temperature No data available : No data available Viscosity Viscosity, kinematic : No data available Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Exposure to air.

10.5. Incompatible materials

oxygen. Do not mix with other chemicals. None known.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue: 12/4/2015 Revision date: 03/24/2015 Version: 1.0 P GHS SDS Page 4 of 8

Safety Data Sheet

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Glycol Ether EB (111-76-2)	
LD50 oral rat	1300 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	1300.000 mg/kg body weight
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
(+)-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE CLP (oral)	4400.000 mg/kg body weight
tetrasodium ethylenediaminetetracet	rate (64-02-8)
LD50 oral rat	> 2000 mg/kg (Rat)
ATE CLP (oral)	500.000 mg/kg body weight
Diethylene Glycol Monoethyl Ether (111-90-0)
LD50 oral rat	1920 mg/kg
Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Glycol Ether EB (111-76-2)	
IARC group	3 - Not Classifiable
(+)-limonene (5989-27-5)	
IARC group	3 - Not Classifiable
Reproductive toxicity	: Not classified
Coopific torget organ toxicity (cingle expe	nours) . Not algorified

Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified.

exposure)

Glycol Ether EB (111-76-2)		
	LOAEL (oral,rat,90 days)	69 mg/kg bodyweight/day Target organ: liver
	NOAEL (dermal,rat/rabbit,90 days)	150 mg/kg bodyweight/day
	Aspiration hazard	: Not classified

Symptoms/injuries after inhalation : Irritation of the nasal mucous membranes. Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Not expected to present a significant ingestion hazard under anticipated conditions of normal

Likely routes of exposure : Skin and eyes contact.;Inhalation

SECTION 12: Ecological information

12.1. Toxicity

Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid

Date of issue: 12/4/2015 Revision date: 03/24/2015 Version: 1.0 P GHS SDS Page 5 of 8

Safety Data Sheet

(+)-limonene (5989-27-5)		
LC50 fish 1	720 µg/l (96 h; Pimephales promelas; Lethal)	
EC50 Daphnia 1	0.36 mg/l (48 h; Daphnia magna; GLP)	
LC50 fish 2	702 μg/l (96 h; Pimephales promelas)	
Threshold limit algae 1	150 mg/l (72 h; Desmodesmus subspicatus; GLP)	
Threshold limit algae 2	2.62 mg/l (72 h; Desmodesmus subspicatus)	
tetrasodium ethylenediaminetetracetate (64-02-8)		
LC50 fish 1	121 mg/l (96 h; Lepomis macrochirus; Soft water)	
EC50 Daphnia 1	625 mg/l (24 h; Daphnia magna)	
LC50 fish 2	374 - 792 mg/l (96 h; Lepomis macrochirus; pH > 7)	
Threshold limit algae 1	> 100 mg/l (72 h; Scenedesmus subspicatus; Growth)	

12.2. Persistence and degradability

(+)-limonene (5989-27-5)		
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.	
ThOD	3.29 g O □/g substance	
tetrasodium ethylenediaminetetracetate (64-02-8)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	< 0.002 g O □/g substance	
Chemical oxygen demand (COD)	0.54 - 0.58 g O□/g substance	

12.3. Bioaccumulative potential

(+)-limonene (5989-27-5)		
BCF fish 1	864.8 - 1022 (Pisces; Fresh weight)	
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)	
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).	
tetrasodium ethylenediaminetetracetate (64-02-8)		
Log Pow	-2.6	
Bioaccumulative potential	Bioaccumulation: not applicable.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Contents under pressure. Do not puncture, incinerate or crush.

Waste disposal recommendations : Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport hazard class(es) (DOT)

In accordance with DOT: Not regulated for transport

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)
: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

 Date of issue: 12/4/2015
 Revision date: 03/24/2015
 Version: 1.0
 P GHS SDS
 Page 6 of 8

Safety Data Sheet

DOT Quantity Limitations Passenger

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft

only (49 CFR 175.75)

: 150 kg

: 75 kg

DOT Vessel Stowage Location

: A

DOT Vessel Stowage Other

: 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information

: This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D

utilizing the exception found at 49 CFR 173.306.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : UN1950
Proper Shipping Name (IMDG) : AEROSOLS

Class (IMDG) : 2.1 - Flammable gases

Air transport

UN-No.(IATA) : UN1950

Proper Shipping Name (IATA) : Aerosols, flammable
Class (IATA) : 2.1 - Gases : Flammable

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Glycol Ether EB (111-76-2)

(+)-limonene (5989-27-5)

propane (74-98-6)

Not listed on SARA Section 313 (Specific toxic chemical listings)

butane (106-97-8)

Not listed on SARA Section 313 (Specific toxic chemical listings)

tetrasodium ethylenediaminetetracetate (64-02-8)

Diethylene Glycol Monoethyl Ether (111-90-0)

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Oral) Acute toxicity (oral) Category 4

Date of issue: 12/4/2015 Revision date: 03/24/2015 Version: 1.0 P GHS SDS Page 7 of 8

Safety Data Sheet

Asp. Tox. 1	Aspiration hazard Category 1
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H226	Flammable liquid and vapor
H227	Combustible liquid
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H373	May cause damage to organs through prolonged or repeated exposure


NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

anicoo prompt medical attention io given

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 12/4/2015
 Revision date: 03/24/2015
 Version: 1.0
 P GHS SDS
 Page 8 of 8